

Wireless Mini Router x

192.168.10.253/home.htm

Router AP

Repeater Wireless ISP

WiFi

Wireless Basic Settings

WAN Basic Setting

Administrat Time Zone

Backup& Reset Management

Firmware Upgrade

Current Mode → Router

Wireless Network

Mode	AP
Band	2.4 GHz (B+G+N)
SSID	Wireless-N
Channel Number	5
Encryption	Disabled
Mac	80:3f:5d:88:d8:3f
Associated Clients	0

Lan Status

Attain IP Protocol	Fixed IP
IP Address	192.168.10.253
Subnet Mask	255.255.255.0
Default Gateway	192.168.10.253
DHCP Server	Enable

WIRELESS-N

192.168.10.253/wzd_wisp.htm

Home Page Advance logout

10:46 13.12.2014

192.168.10.253/wzd_rep.htm

192.168.10.253/wzd_rep.htm

Wizard -- Repeater mode

Refresh

SSID	Mac	Channel	Encrypt	Signal	Select
S-LINK	64:51:7e:18:23:cb	1 B+G	WPA2-PSK	100%	Select
SNOPY	78:44:76:0a:bb:28	11 B+G+N	WPA- PSK/WPA2- PSK	100%	Select
Tenda	c8:3a:35:5a:ab:21	11 B+G+N	WPA-PSK	75%	Select
Segment-Satis	c8:3a:35:39:7a:00	11 B+G+N	WPA- PSK/WPA2- PSK	55%	Select

Save&Reboot

WIRELESS-N

Home Page Advance logout

Style

10:48
13.12.2014

Baglanmak istediginiz modemin karşısındaki select tuşuna basınız

192.168.10.253/wzd_rep.htm

192.168.10.253/wzd_rep.htm

Wizard -- Repeater mode

Refresh

Connect to: SNOPY

SSID: Wireless-N

Key:

Save&Reboot

WIRELESS-N

Home Page Advance logout

Style

10:49
13.12.2014

Baglanacaginiz modemin ismi

cihazınızın adı istenildiginde degisebilir

Baglanmak istediginiz modemin kablosuz şifresini yazınız

kaydet

GÜVENLİK ENGELİ OLAN MODEMLERDE YAPILACAK AYARLAR

LAN Interface Setup

192.168.2.99/tcpiplan.htm

LAN

IP Address : 192.168.2.99

Sub Net : 255.255.255.0

Default Gateway : 192.168.2.1

DHCP: Server

DHCP Client Range : 192.168.2.100 - 192.168.2.200

DHCP Lease Time : 480 (1 ~ 10080 minutes)

802.1d Spanning Tree : Disable

Apply Reset

WIRELESS-N

Home Page Advance logout

Style

13:34
13.12.2014